

Dry powder Fire Extinguisher

Product Data Sheet



DRY POWDER PORTABLE TYPE FIRE EXTINGUISHER

Model	FRND B1	FRNDC 1	FRNDB 2	FRNDC 2	FRNDB 4	FRNDB 6	FRNDB 9	FRNDA 6	FRNRA 6	FRNRB 6
Capacity	1 KG	1 KG	2 KG	2 KG	4 KG	6 KG	9 KG	6 KG	6 KG	6 KG
Total Weight	1.98 KG	1.98 KG	3.6 KG	3.6 KG	6.1 KG	9.4 KG	13.1 KG	9.4 KG	9.4 KG	9.4 KG
Cylinder Height (mm)	315	315	391	391	483	494	556	494	494	494
Cylinder Diameter (mm)	91	91	110	110	130	163	183	163	163	163
Range of Throw	3.5	3.5	4.0	4.0	5.0	5.5	6.0	5.5	5.5	5.5
Fire Rating	8A &55B	5A & 34B	13A & 89B	13A & 70B	27A &183B	43A & 233B	55A & 233B	55A & 233B	55A & 233B	43A & 233B
Duration of Discharge (sec)	8	8	10	10	17	17	23	17	17	17
Extinguishing Agent	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder	40% ABC Powder
Propelling Agent	N ₂	N ₂	N ₂	N ₂	N ₂	N ₂	N ₂	N ₂	N ₂	N ₂
Working Pressure	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar	14 Bar
Material	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon	Steel Low Carbon
Operating Temperature	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C	-30C to +60C