

FRN 60

Intelligent Addressable Fire Alarm Manual Call Point



Product Features:

- Semi-flush or surface mount.
- Lever reusable (non-glass break).
- LED indicator.
- Support non-polarity, complete soft addressing in situ.
- Designed with passive output contacts to control other external equipment directly via an intermediate relay.
- Comply with EN54-11.

| | |
|---------------------------|---|
| Operating Voltage | Loop 24V (18V~28V) |
| Standby Current | <0.3mA |
| Alarm Current | <2mA |
| Indicator | Red alarm indicator flashes when data logging, press the manual button lit work |
| Type of Initiating Part | Reusable |
| Initiating Mode | Pressing the frangible element manually |
| Resuming Mode | Manually resumed by a special key |
| Programming Mode | Electronically addressed |
| Address Range | One address within 1~324. |
| Wiring | Polarity-insensitive two-wire |
| Class | Type A, indoors. |
| Ingress Protection Rating | IP43 |
| Environmental Temperature | -10°C~+55°C |
| Relative Humidity | ≤95%, non-condensing |
| Material of Enclosure | ABS |
| Dimension (L×W×H) | 90mm×90mm×42mm (overall height) 90mm×90mm×23mm (exposed after installation dimensions) |
| Mounting Hole Distance | 60mm ~ 62.5mm |
| Weight | About 95g |